

BM N系列塑壳断路器

| 壳架等级额定电流 | 额定短路分断能力 (kA) | | | | | | | 极数 (P) | 额定电流 In(A) | 附属装置 | |
|----------|---------------|-----------|------|------------|------|------|------|--------|-----------------------------|--|-------|
| | 等级代号 | GB14048.2 | | IEC60947-2 | | | | | | | |
| | | 230V | 400V | 220V | 380V | 440V | 500V | | | | |
| 30 | CN | 2.5 | 1.5 | 2.5 | 1.5 | - | - | 2,3 | 3,5,10,15,20,30 | 代号 | 说明 |
| | SN | 5 | 2.5 | 5 | 2.5 | 2.5 | 1.5 | 3 | | 空白 | 无附属装置 |
| 60 | SN | 10 | 7.5 | 10 | 7.5 | 7.5 | 5 | 3 | 10,15,20,30,40,50,60 | AX | 辅助开关 |
| | HN | 25 | 10 | 25 | 15 | 10 | 5 | 3 | | AL | 报警开关 |
| | HBN | 50 | 25 | 50 | 30 | 25 | 15 | 3 | | SHT | 分励脱扣器 |
| | SN | 25 | 10 | 25 | 15 | 10 | 5 | 3 | | UVT | 欠压脱扣器 |
| 100 | HN | 50 | 25 | 50 | 30 | 25 | 15 | 3,4 | 10,15,20,30,40,50,60,75,100 | 注1: 100H、100HC、100HS, 30A及以下规格无分励脱扣器 注2: 100H、100HC、100HS、160HB、160HC、160HS、250HB、250HC、250HS 无UVT欠压脱扣器 | |
| | HBN | 85 | 36 | 85 | 36 | 32 | 20 | 3,4 | | | |
| | H | 85 | 50 | 85 | 50 | 42 | 25 | 3 | 15,20,30,40,50,60,75,100 | | |
| | HC | 100 | 70 | 100 | 70 | 55 | 42 | 3,4 | 40,50,63,80,100 | | |
| | HS | 125 | 85 | 125 | 85 | 70 | 50 | 3,4 | | | |
| | SN | 50 | 25 | 50 | 30 | 25 | 15 | 3,4 | | | |
| 160 | HN | 85 | 36 | 85 | 36 | 32 | 20 | 3,4 | 125,140,160 | | |
| | HB | 85 | 50 | 85 | 50 | 42 | 25 | 3,4 | | | |
| | HC | 100 | 70 | 100 | 70 | 55 | 42 | 3,4 | | | |
| | HS | 125 | 85 | 125 | 85 | 70 | 50 | 3,4 | | | |
| 250 | SN | 50 | 25 | 50 | 30 | 25 | 15 | 3,4 | 175,200,225,250 | | |
| | HN | 85 | 36 | 85 | 36 | 32 | 20 | 3,4 | | | |
| | HB | 85 | 50 | 85 | 50 | 42 | 25 | 3,4 | 125,150,175,200,225,250 | | |
| | HC | 100 | 70 | 100 | 70 | 55 | 42 | 3,4 | 175,200,225,250 | | |
| | HS | 125 | 85 | 125 | 85 | 70 | 50 | 3,4 | | | |
| 400 | SN | 50 | 35 | 50 | 35 | 30 | 20 | 3,4 | 250,300,350,400 | | |
| | HN | 85 | 50 | 85 | 50 | 42 | 25 | 3,4 | | | |
| | RN | 100 | 70 | 100 | 70 | 55 | 42 | 3,4 | | | |
| | UN | 125 | 85 | 125 | 85 | 85 | 65 | 3,4 | | | |
| 630 | SN | 50 | 35 | 50 | 35 | 30 | 20 | 3,4 | 500,630 | | |
| | HN | 85 | 50 | 85 | 50 | 50 | 25 | 3,4 | | | |
| | RN | 100 | 70 | 100 | 70 | 70 | 42 | 3,4 | | | |
| | UN | 125 | 85 | 125 | 100 | 85 | 65 | 3,4 | | | |

BM N系列塑壳断路器 (续表)

| 壳架等级额定电流 | 等级代号 | 额定短路分断能力 (kA) | | | | | | 极数 (P) | 额定电流 In(A) | 附属装置 | |
|----------|------|---------------|------|------------|------|------|------|--------|------------|------|-------|
| | | GB14048.2 | | IEC60947-2 | | | | | | | |
| | | 230V | 400V | 220V | 380V | 440V | 500V | | | | |
| 800 | CN | 50 | 35 | 50 | 35 | 30 | 20 | 3,4 | 700,800 | 代号 | 说明 |
| | SN | 85 | 50 | 85 | 50 | 50 | 25 | 3,4 | | 空白 | 无附属装置 |
| | HN | 100 | 70 | 100 | 70 | 70 | 42 | 3,4 | | AX | 辅助开关 |
| | RN | 125 | 85 | 125 | 100 | 85 | 65 | 3,4 | | AL | 报警开关 |
| | | | | | | | | | | SHT | 分励脱扣器 |
| 1000 | HS | 130 | 85 | 130 | 100 | 85 | 65 | 3 | 1000 | UVT | 欠压脱扣器 |
| 1200 | HS | 130 | 85 | 130 | 100 | 85 | 65 | 3 | 1200 | | |
| 1600 | HS | 130 | 85 | 130 | 100 | 85 | 65 | 3 | 1400,1600 | | |

BL N系列塑壳断路器

| 壳架等级额定电流 | 等级代号 | 额定短路分断能力 (kA) | | | | | 极数 (P) | 额定电流 (A) | 附属装置 | | |
|----------|------|---------------|------|------------|------|------|--------|--------------------------|-----------------|-------|--------|
| | | GB14048.2 | | IEC60947-2 | | | | | | | |
| | | 230V | 400V | 220V | 380V | 440V | | | | | |
| 50 | SN | 10 | 7.5 | 10 | 7.5 | 7.5 | 3,4 | 15,20,30,40,50 | 代号 | 说明 | |
| 100 | SN | 25 | 10 | 25 | 15 | 10 | 3,4 | 15,20,30,40,50,60,75,100 | 空白 | 无附属装置 | |
| | HN | 50 | 25 | 50 | 30 | 25 | 3,4 | | AX | 辅助开关 | |
| 160 | SN | 50 | 25 | 50 | 30 | 25 | 3,4 | 125,140,160 | AL | 报警开关 | |
| 250 | SN | 50 | 25 | 50 | 30 | 25 | 3,4 | 175,200,225,250 | SHT | 分励脱扣器 | |
| | | | | | | | | | UVT | 欠压脱扣器 | |
| | SN | 50 | 35 | 50 | 35 | 30 | 3,4 | | 250,300,350,400 | AM | 漏电报警模块 |
| | HN | 85 | 50 | 85 | 50 | 42 | 3,4 | | | | |
| | RN | 100 | 70 | 100 | 70 | 55 | 3,4 | | | | |
| 400 | UN | 125 | 85 | 125 | 85 | 85 | 3,4 | | | | |
| | HN | 85 | 50 | 85 | 50 | 50 | 3,4 | 500,630 | | | |
| | RN | 100 | 70 | 100 | 70 | 70 | 3,4 | | | | |
| UN | 125 | 85 | 125 | 100 | 85 | 3,4 | | | | | |
| 630 | SN | 85 | 50 | 85 | 50 | 50 | 3,4 | 700,800 | | | |
| | HN | 100 | 70 | 100 | 70 | 70 | 3,4 | | | | |
| | RN | 125 | 85 | 125 | 100 | 85 | 3,4 | | | | |
| 800 | SN | 85 | 50 | 85 | 50 | 50 | 3,4 | | | | |
| | HN | 100 | 70 | 100 | 70 | 70 | 3,4 | | | | |
| | RN | 125 | 85 | 125 | 100 | 85 | 3,4 | | | | |


注1: 50SN
无UVT欠压脱扣器

塑壳断路器分断能力一览表

| 产品类别 | 额定短路分断能力 (kA) | 壳架等级额定电流 Inm (A) | | | | | | | | | | |
|------------|---------------|--------------------|---------|---------|--------|--------|--------|--------|--------|----------|----------|----------|
| | | GB14048.2 | | AC 400V | | | | | | | | |
| | | 30 | 50/60 | 100 | 160 | 250 | 400 | 630 | 800 | 1000 | 1200 | 1600 |
| 塑壳断路器 (BM) | 85kA | | | 100-HS | 160-HS | 250-HS | 400-UN | 630-UN | 800-RN | 1000-HS* | 1200-HS* | 1600-HS* |
| | 70kA | | | 100-HC | 160-HC | 250-HC | 400-RN | 630-RN | 800-HN | | | |
| | 50kA | | | 100-H* | 160-HB | 250-HB | 400-HN | 630-HN | 800-SN | | | |
| | 35/36kA | | | 100-HBN | 160-HN | 250-HN | 400-SN | 630-SN | 800-CN | | | |
| | 25kA | | 60-HBN* | 100-HN | 160-SN | 250-SN | | | | | | |
| | 10kA | | 60-HN* | 100-SN* | | | | | | | | |
| | 7.5kA | | 60-SN* | | | | | | | | | |
| | 2.5kA | 30-SN* | | | | | | | | | | |
| | 1.5kA | 30-CN [®] | | | | | | | | | | |
| | 漏电断路器 (BL) | 85kA | | | | | | 400-UN | 630-UN | 800-RN | | |
| 70kA | | | | | | | 400-RN | 630-RN | 800-HN | | | |
| 50kA | | | | | | | 400-HN | 630-HN | 800-SN | | | |
| 35kA | | | | | | | 400-SN | | | | | |
| 25kA | | | | 100-HN | 160-SN | 250-SN | | | | | | |
| 10kA | | | | 100-SN | | | | | | | | |
| 7.5kA | | | 50-SN | | | | | | | | | |

注: “*”表示有3P机种。“[®]”表示有2P及3P机种,未标注表示有3P及4P机种。

BM N系列塑壳断路器

| 壳架等级额定电流 (Inm) | | 30 | | 60 | | |
|--|---|---------------------|------|---------------------|------|--|
| 型 号 | | BM30-CN | | BM30-SN | | |
| 额定电流In(A) 整定温度40℃ | | 3,5,10, 15,20,30 | | 3,5,10, 15,20,30 | | |
| 极 数 (P) | | 2 | 3 | 3 | 3 | |
| 额定绝缘电压Ui(V) | AC | 500 | | 690 | | |
| | DC | 250 | | 250 | | |
| 外形及安装尺寸  | a | 45 | 67.5 | 75 | 75 | |
| | b | 96 | | 130 | | |
| | c | 52 | | 68 | | |
| | ca | 67 | | 90 | | |
| | bb | 84 | | 111 | | |
| | aa | 23.5 | | 25 | | |
| | 重量 (kg) | 0.3 | 0.4 | 0.65 | 0.65 | |
| 短路分断能力(Icu) | GB 14048.2 AC Icu (kA) | 400V | 1.5 | 2.5 | 7.5 | |
| | | 230V | 2.5 | 5 | 10 | |
| | IEC 60947-2 EN 60947-2 AC Icu(kA) | 500V | - | 1.5 | 5 | |
| | | 440V | - | 2.5 | 7.5 | |
| | | 380V | 1.5 | 2.5 | 7.5 | |
| | | 220V(240V) | 2.5 | 5 | 10 | |
| | DC | 250V | - | - | - | |
| | | 125V | - | - | - | |
| 接线方式 | | 压接端子 | | 压接端子 | | |
| 选购附件 | 报警开关 (AL) | - | ○ | ○ | | |
| | 辅助开关 (AX) | - | ○ | ○ | | |
| | 分励脱扣器 (SHT) | - | ○ | ○ | | |
| | 欠压脱扣器 (UVT) | - | ○ | ○ | | |
| | 外部操作把手 (EH) | - | ● | ● | | |
| | 端子隔离盖 | ● | ● | ● | | |
| 脱扣器 | | 完全电磁式 | | 完全电磁式 | | |
| 脱扣按钮 | | - | 有 | 有 | | |

注：“●”代表嵌入式可由客户自行安装；“○”为内装式须由工厂安装；“-”表示无此附件

| 60 | | 100 | |
|---------------------------------|--|---------------------------------|--|
| BM60-HN | | BM60-HBN | |
| 10,15,20 30,40,50,60 | | 10,15,20 30,40,50,60 | |
| 10,15,20,30, 40,50,60,75,100 | | 10,15,20,30, 40,50,60,75,100 | |
| 3 | | 3 | |
| 690 | | 690 | |
| 250 | | 250 | |
| 75 | | 90 | |
| 130 | | 155 | |
| 68 | | 68 | |
| 90 | | 90 | |
| 111 | | 134 | |
| 25 | | 30 | |
| 0.65 | | 1.3 | |
| 10 | | 25 | |
| 25 | | 50 | |
| 5 | | 15 | |
| 10 | | 25 | |
| 15 | | 30 | |
| 25 | | 50 | |
| - | | - | |
| - | | - | |
| 压接端子 | | 压接端子 | |
| ○ | | ○ | |
| ○ | | ○ | |
| ○ | | ○ | |
| ○ | | ○ | |
| ● | | ● | |
| ● | | ● | |
| 完全电磁式 | | 完全电磁式 | |
| 有 | | 有 | |

BM N系列塑壳断路器

| 壳架等级额定电流 (Inm) | | 100 | | | | | |
|--|--------------------------------------|---------------------|------|------------------------------|------|---------------------|--|
| 型号 | | BM100-HBN | | BM100-H | | BM100-HC | |
| 额定电流In(A) 整定温度40℃ | | 40,50,63, 80,100 | | 15,20,30,40, 50,60,75,100 | | 40,50,63, 80,100 | |
| 极数(P) | | 3 | 4 | 3 | 3 | 4 | |
| 额定绝缘电压Ui(V) | AC | 690 | | 690 | | 690 | |
| | DC | 250 | | 250 | | 250 | |
| 外形及安装尺寸  | a | 105 | 140 | 105 | 105 | 140 | |
| | b | 165 | | 165 | | 165 | |
| | c | 68 | | 86 | | 86 | |
| | ca | 92 | | 112 | | 112 | |
| | bb | 126 | | 126 | | 126 | |
| | aa | 35 | | 35 | | 35 | |
| | 重量(kg) | 1.5 | 1.9 | 2.1 | 2.1 | 2.6 | |
| 短路分断能力(Icu) | GB 14048.2 AC Icu(kA) | 400V | 36 | 50 | 70 | | |
| | | 230V | 85 | 85 | 100 | | |
| | IEC 60947-2 AC EN 60947-2 Icu(kA) | 500V | 20 | 25 | 42 | | |
| | | 440V | 32 | 42 | 55 | | |
| | | 380V | 36 | 50 | 70 | | |
| | | 220V(240V) | 85 | 85 | 100 | | |
| | DC | 250V | - | - | - | | |
| | | 125V | - | - | - | | |
| 接线方式 | | 压接端子 | | 压接端子 | | 压接端子 | |
| 选购附件 | 报警开关 (AL) | ● | ○ | ○ | | | |
| | 辅助开关 (AX) | ● | ○ | ○ | | | |
| | 分励脱扣器 (SHT) | ● | ○ | ○ | | | |
| | 欠压脱扣器 (UVT) | ● | - | - | | | |
| | 外部操作把手 (EH) | ● | ● | ● | | | |
| | 端子隔离盖 | ● | ● | ● | | | |
| 脱扣器 | 可调热动-电磁式 | | 热-磁式 | | 热-磁式 | | |
| 脱扣按钮 | 有 | | 有 | | 有 | | |

注：“●”代表嵌入式可由客户自行安装；“○”为内装式须由工厂安装；“-”表示无此附件

| 100 | | 160 | | | | | |
|---------------------|----------|-------------|----------|-------------|------|-------------|------|
| BM100-HS | | BM160-SN | | BM160-HN | | BM160-HB | |
| 40,50, 63,80,100 | | 125,140,160 | | 125,140,160 | | 125,140,160 | |
| 3 | 4 | 3 | 4 | 3 | 4 | 3 | 4 |
| 690 | | 690 | | 690 | | 690 | |
| 250 | | 250 | | 250 | | 250 | |
| 105 | 140 | 105 | 140 | 105 | 140 | 105 | 140 |
| 165 | | 165 | | 165 | | 165 | |
| 86 | | 68 | | 68 | | 86 | |
| 112 | | 92 | | 92 | | 112 | |
| 126 | | 126 | | 126 | | 126 | |
| 35 | | 35 | | 35 | | 35 | |
| 2.1 | 2.6 | 1.5 | 1.9 | 1.5 | 1.9 | 2.1 | 2.6 |
| 85 | | 25 | | 36 | | 50 | |
| 125 | | 50 | | 85 | | 85 | |
| 50 | | 15 | | 20 | | 25 | |
| 70 | | 25 | | 32 | | 42 | |
| 85 | | 30 | | 36 | | 50 | |
| 125 | | 50 | | 85 | | 85 | |
| - | | - | | - | | - | |
| - | | - | | - | | - | |
| 压接端子 | | 压接端子 | | 压接端子 | | 压接端子 | |
| ○ | ● | ● | ● | ● | ○ | ○ | ○ |
| ○ | ● | ● | ● | ● | ○ | ○ | ○ |
| ○ | ● | ● | ● | ● | ○ | ○ | ○ |
| - | ● | ● | ● | ● | - | - | - |
| ● | ● | ● | ● | ● | ● | ● | ● |
| ● | ● | ● | ● | ● | ● | ● | ● |
| 热-磁式 | 可调热动-电磁式 | 可调热动-电磁式 | 可调热动-电磁式 | 热-磁式 | 热-磁式 | 热-磁式 | 热-磁式 |
| 有 | 有 | 有 | 有 | 有 | 有 | 有 | 有 |


BM N系列塑壳断路器

| 壳架等级额定电流 (Inm) | | 160 | | | | 250 | |
|--|---|-------------|-----|-------------|-----|---------------------|-----|
| 型 号 | | BM160-HC | | BM160-HS | | BM250-SN | |
| 额定电流In(A) 整定温度40℃ | | 125,140,160 | | 125,140,160 | | 175,200, 225,250 | |
| 极 数 (P) | | 3 | 4 | 3 | 4 | 3 | 4 |
| 额定绝缘电压Ui(V) | AC | 690 | | 690 | | 690 | |
| | DC | 250 | | 250 | | 250 | |
| 外形及安装尺寸  | a | 105 | 140 | 105 | 140 | 105 | 140 |
| | b | 165 | | 165 | | 165 | |
| | c | 86 | | 86 | | 68 | |
| | ca | 112 | | 112 | | 92 | |
| | bb | 126 | | 126 | | 126 | |
| | aa | 35 | | 35 | | 35 | |
| | 重量 (kg) | 2.1 | 2.6 | 2.1 | 2.6 | 1.5 | 1.9 |
| 短路分断能力(Icu) | GB 14048.2 AC Icu(kA) | 400V | 70 | 85 | 25 | | |
| | | 230V | 100 | 125 | 50 | | |
| | IEC 60947-2 EN 60947-2 AC Icu(kA) | 500V | 42 | 50 | 15 | | |
| | | 440V | 55 | 70 | 25 | | |
| | | 380V | 70 | 85 | 30 | | |
| | 220V(240V) | 100 | 125 | 50 | | | |
| | DC | 250V | - | - | - | | |
| 125V | | - | - | - | | | |
| 接线方式 | | 压接端子 | | 压接端子 | | 压接端子 | |
| 选购附件 | 报警开关 (AL) | ○ | ○ | ● | | | |
| | 辅助开关 (AX) | ○ | ○ | ● | | | |
| | 分励脱扣器 (SHT) | ○ | ○ | ● | | | |
| | 欠压脱扣器 (UVT) | - | - | ● | | | |
| | 外部操作把手 (EH) | ● | ● | ● | | | |
| | 端子隔离盖 | ● | ● | ● | | | |
| 脱扣器 | | 热-磁式 | | 热-磁式 | | 可调热动-电磁式 | |
| 脱扣按钮 | | 有 | | 有 | | 有 | |

注：“●”代表嵌入式可由客户自行安装；“○”为内装式须由工厂安装；“-”表示无此附件

| 250 | | | | | | | |
|-----------------|-----|-----------------------------|-----|-----------------|-----|-----------------|-----|
| BM250-HN | | BM250-HB | | BM250-HC | | BM250-HS | |
| 175,200,225,250 | | 125,150,175, 200,225,250 | | 175,200,225,250 | | 175,200,225,250 | |
| 3 | 4 | 3 | 4 | 3 | 4 | 3 | 4 |
| 690 | | 690 | | 690 | | 690 | |
| 250 | | 250 | | 250 | | 250 | |
| 105 | 140 | 105 | 140 | 105 | 140 | 105 | 140 |
| 165 | | 165 | | 165 | | 165 | |
| 68 | | 86 | | 86 | | 86 | |
| 92 | | 112 | | 112 | | 112 | |
| 126 | | 126 | | 126 | | 126 | |
| 35 | | 35 | | 35 | | 35 | |
| 1.5 | 1.9 | 2.1 | 2.6 | 2.1 | 2.6 | 2.1 | 2.6 |
| 36 | | 50 | | 70 | | 85 | |
| 85 | | 85 | | 100 | | 125 | |
| 20 | | 25 | | 42 | | 50 | |
| 32 | | 42 | | 55 | | 70 | |
| 36 | | 50 | | 70 | | 85 | |
| 85 | | 85 | | 100 | | 125 | |
| - | | - | | - | | - | |
| - | | - | | - | | - | |
| 压接端子 | | 压接端子 | | 压接端子 | | 压接端子 | |
| ● | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| ● | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| ● | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| ● | - | - | - | - | - | - | - |
| ● | ● | ● | ● | ● | ● | ● | ● |
| ● | ● | ● | ● | ● | ● | ● | ● |
| 可调热动-电磁式 | | 热-磁式 | | 热-磁式 | | 热-磁式 | |
| 有 | | 有 | | 有 | | 有 | |

BM N系列塑壳断路器

| 壳架等级额定电流 (Inm) | | 400 | | | | | |
|--|---|-----------------|-----|-----------------|-----|-----------------|-----|
| 型 号 | | BM400-SN | | BM400-HN | | BM400-RN | |
| 额定电流In(A) 整定温度40℃ | | 250,300,350,400 | | 250,300,350,400 | | 250,300,350,400 | |
| 极 数 (P) | | 3 | 4 | 3 | 4 | 3 | 4 |
| 额定绝缘电压Ui(V) | AC | 690 | | 690 | | 690 | |
| | DC | 250 | | 250 | | 250 | |
| 外形及安装尺寸  | a | 140 | 185 | 140 | 185 | 140 | 185 |
| | b | 257 | | 257 | | 257 | |
| | c | 103 | | 103 | | 103 | |
| | ca | 155 | | 155 | | 155 | |
| | bb | 194 | | 194 | | 194 | |
| | aa | 44 | | 44 | | 44 | |
| | 重量 (kg) | 5.7 | 7.5 | 5.7 | 7.5 | 5.7 | 7.5 |
| 短路分断能力(kA) | GB 14048.2 AC Icu(kA) | 400V | 35 | 50 | 70 | | |
| | | 230V | 50 | 85 | 100 | | |
| | | 500V | 20 | 25 | 42 | | |
| | IEC 60947-2 EN 60947-2 AC Icu(kA) | 440V | 30 | 42 | 55 | | |
| | | 380V | 35 | 50 | 70 | | |
| | | 220V(240V) | 50 | 85 | 100 | | |
| | DC | 250V | - | - | - | | |
| 125V | | - | - | - | | | |
| 接线方式 | | 铜接板 | | 铜接板 | | 铜接板 | |
| 选购附件 | 报警开关 (AL) | ● | ● | ● | | | |
| | 辅助开关 (AX) | ● | ● | ● | | | |
| | 分励脱扣器 (SHT) | ● | ● | ● | | | |
| | 欠压脱扣器 (UVT) | ● | ● | ● | | | |
| | 外部操作把手 (EH) | ● | ● | ● | | | |
| | 端子隔离盖 | ● | ● | ● | | | |
| 脱扣器 | | 热-磁式 | | 热-磁式 | | 热-磁式 | |
| 脱扣按钮 | | 有 | | 有 | | 有 | |

注：“●”代表嵌入式可由客户自行安装；“○”为内装式须由工厂安装；“-”表示无此附件

| 400 | | 630 | | | | | |
|-----------------|-----|----------|-----|----------|-----|----------|-----|
| BM400-UN | | BM630-SN | | BM630-HN | | BM630-RN | |
| 250,300,350,400 | | 500,630 | | 500,630 | | 500,630 | |
| 3 | 4 | 3 | 4 | 3 | 4 | 3 | 4 |
| 690 | | 690 | | 690 | | 690 | |
| 250 | | 250 | | 250 | | 250 | |
| 140 | 185 | 210 | 280 | 210 | 280 | 210 | 280 |
| 257 | | 275 | | 275 | | 275 | |
| 103 | | 103 | | 103 | | 103 | |
| 155 | | 155 | | 155 | | 155 | |
| 194 | | 243 | | 243 | | 243 | |
| 44 | | 70 | | 70 | | 70 | |
| 5.7 | 7.5 | 10 | 13 | 10 | 13 | 10 | 13 |
| 85 | | 35 | | 50 | | 70 | |
| 125 | | 50 | | 85 | | 100 | |
| 65 | | 20 | | 25 | | 42 | |
| 85 | | 30 | | 50 | | 70 | |
| 85 | | 35 | | 50 | | 70 | |
| 125 | | 50 | | 85 | | 100 | |
| - | | 20 | - | 40 | - | - | |
| - | | - | | - | | - | |
| 铜接板 | | 铜接板 | | 铜接板 | | 铜接板 | |
| ● | ● | ● | ● | ● | ● | ● | ● |
| ● | ● | ● | ● | ● | ● | ● | ● |
| ● | ● | ● | ● | ● | ● | ● | ● |
| ● | ● | ● | ● | ● | ● | ● | ● |
| ● | ● | ● | ● | ● | ● | ● | ● |
| ● | ● | ● | ● | ● | ● | ● | ● |
| 热-磁式 | | 热动-可调电磁式 | | 热动-可调电磁式 | | 热动-可调电磁式 | |
| 有 | | 有 | | 有 | | 有 | |

BM系列塑壳断路器

| 壳架等级额定电流 (Inm) | | 630 | | 800 | | | |
|--|---------------------------|------------|-----|----------|------|----------|------|
| 型号 | | BM630-UN | | BM800-CN | | BM800-SN | |
| 额定电流In(A) | | 500,630 | | 700,800 | | 700,800 | |
| 整定温度40℃ | | | | | | | |
| 极数(P) | | 3 | 4 | 3 | 4 | 3 | 4 |
| 额定绝缘电压Ui(V) | AC | 690 | | 690 | | 690 | |
| | DC | 250 | | 250 | | 250 | |
| 外形及安装尺寸  | a | 210 | 280 | 210 | 280 | 210 | 280 |
| | b | 275 | | 275 | | 275 | |
| | c | 103 | | 103 | | 103 | |
| | ca | 155 | | 155 | | 155 | |
| | bb | 243 | | 243 | | 243 | |
| | aa | 70 | | 70 | | 70 | |
| | 重量(kg) | 10 | 13 | 10.5 | 13.5 | 10.5 | 13.5 |
| 短路分断能力(Icu) | GB 14048.2 AC | 400V | 85 | 35 | 50 | | |
| | | 230V | 125 | 50 | 85 | | |
| | | 500V | 65 | 20 | 25 | | |
| | IEC 60947-2 EN 60947-2 AC | 440V | 85 | 30 | 50 | | |
| | | 380V | 100 | 35 | 50 | | |
| | | 220V(240V) | 125 | 50 | 85 | | |
| | DC | 250V | - | 20 | - | 40 | - |
| 125V | | - | - | - | - | - | |
| 接线方式 | | 铜接板 | | 铜接板 | | 铜接板 | |
| 选购附件 | 报警开关 (AL) | ● | ● | ● | ● | ● | ● |
| | 辅助开关 (AX) | ● | ● | ● | ● | ● | ● |
| | 分励脱扣器 (SHT) | ● | ● | ● | ● | ● | ● |
| | 欠压脱扣器 (UVT) | ● | ● | ● | ● | ● | ● |
| | 外部操作把手 (EH) | ● | ● | ● | ● | ● | ● |
| | 端子隔离盖 | ● | ● | ● | ● | ● | ● |
| 脱扣器 | | 热动-可调电磁式 | | 热动-可调电磁式 | | 热动-可调电磁式 | |
| 脱扣按钮 | | 有 | | 有 | | 有 | |

注：“●”代表嵌入式可由客户自行安装；“○”为内装式须由工厂安装；“-”表示无此附件

| 800 | | 1000 | | 1200 | | 1600 | | | |
|----------|------|----------|------|-----------|-----|-----------|--|-----------|--|
| BM800-HN | | BM800-RN | | BM1000-HS | | BM1200-HS | | BM1600-HS | |
| 700,800 | | 700,800 | | 1000 | | 1200 | | 1400,1600 | |
| 3 | 4 | 3 | 4 | 3 | 3 | 3 | | | |
| 690 | | 690 | | 690 | | 690 | | 690 | |
| 250 | | 250 | | - | | - | | - | |
| 210 | 280 | 210 | 280 | 210 | 210 | 210 | | | |
| 275 | | 275 | | 406 | | 406 | | 406 | |
| 103 | | 103 | | 140 | | 140 | | 140 | |
| 155 | | 155 | | 190 | | 190 | | 190 | |
| 243 | | 243 | | 375 | | 375 | | 375 | |
| 70 | | 70 | | 70 | | 70 | | 70 | |
| 10.5 | 13.5 | 10.5 | 13.5 | 23 | 23 | 23 | | | |
| 70 | | 85 | | 85 | | 85 | | 85 | |
| 100 | | 125 | | 130 | | 130 | | 130 | |
| 42 | | 65 | | 65 | | 65 | | 65 | |
| 70 | | 85 | | 85 | | 85 | | 85 | |
| 70 | | 100 | | 100 | | 100 | | 100 | |
| 100 | | 125 | | 130 | | 130 | | 130 | |
| - | | - | | - | | - | | - | |
| - | | - | | - | | - | | - | |
| 铜接板 | | 铜接板 | | 铜接板 | | 铜接板 | | 铜接板 | |
| ● | ● | ○ | ○ | ○ | ○ | ○ | | | |
| ● | ● | ○ | ○ | ○ | ○ | ○ | | | |
| ● | ● | ○ | ○ | ○ | ○ | ○ | | | |
| ● | ● | ○ | ○ | ○ | ○ | ○ | | | |
| ● | ● | - | - | - | - | - | | | |
| ● | ● | - | - | - | - | - | | | |
| 热动-可调电磁式 | | 热动-可调电磁式 | | 热动-可调电磁式 | | 热动-可调电磁式 | | 热动-可调电磁式 | |
| 有 | | 有 | | 有 | | 有 | | 有 | |